

DATA SHEET

PM-1216/1217/1218F-9

Rear Fog Light



Images

LumenX




Rear of light showing built-in AMP compatible receptacle & plug




PM-B426-18 grommet




Dimensions




Surface mount with bracket



PM-1217F-9 light module



Flange mount



PM-B426-18 grommet



Specifications

Functions:	LED rear fog light
LEDs:	9 x LEDs
Lens type:	LumenX®
Lens colour:	Red
Certifications:	ECE Reg 38
Voltage:	Dual voltage 12/24Vdc
IP rating:	IP67
Operating temperature:	-30°C to +50°C
Mounting:	PM-1216F & 1216FC surface mount with bracket PM-1217F-9 surface mounts using a PM-B817 series bracket or flush mounts using PM-B426-18 grommet PM- 1218F-9 flange mounts
Wiring:	Built-in AMP-compatible receptacle for direct attachment to body harness, or requires PM-B417-48 or PM-B817-48 plug AMP Terminals: T1 = ground T2 = not used T3 = fog
Power rating:	6.0W @ 12V / 6.0W @ 24V
Average current draw:	0.50A @ 12V / 0.25A @ 24V
Reverse polarity protection:	Yes
Warranty:	3 years



Materials

Lens:	PMMA-HI
Base:	ABS

Part numbers

PM-1216F-9	LED rear fog light- surface mount, black bracket
PM-1216FC-9	LED rear fog light- surface mount, chrome bracket
PM-1217F-9	LED rear fog light module- (see mounting options below)
PM-1218F-9	LED rear fog light - flange mount
PM-B817-09	Black bracket for PM-1217F-9 (surface mounting)
PM-B817-10	Chrome bracket for PM-1217F-9 (surface mounting)
PM-B426-18	Grommet for PM-1217F-9 (flush mounting)
PM-B417-48	2 wire plug
PM-B817-48	2 wire plug (moulded)